

- Kabylake
- Fanless
- HDMI
- DP
- SIM Slot
- Type-C



RoHS  

Features

- Intel® 7th Generation Core Processors
- 2 x SO-DIMM DDR3L, Up to 32GB
- 1 x DP, 1 x HDMI2.0, 1 x VGA
- 1 x 2.5" SATA, 1 x mSATA, 1 x M.2 for SSD
- 1 x Type-C USB3.0, 3 x USB3.0, 2 x USB2.0, 4 x RS232, 2 x RS485
- 2 x RJ45, 1 x Mini-PCIe for WiFi/BT/3G/4G, 1 x SIM Slot

Specifications

CPU	Intel® Core i3-7100U/Core i5-7200U
Frequency	2.40 GHz/2.50 GHz up to 3.10 GHz
BIOS	AMI Source Code
Chipset	SOC
System Memory	2 x SO-DIMM, DDR3L-1600MHz, Up to 32GB
GPU	Intel® HD Graphics 620
Graphic Engine	Direct3D 2015, OpenGL 4.5, OpenCL 2.1
Display Interface	1 x HDMI (Max. 3840*2160 @60HZ) 1 x DP (Max. 4096 x 2304 @60Hz) 1 x VGA (Max. 2048 x 1536 @60Hz)
Network Controller	1 x Intel I211, 1 x Intel I219, Gigabit Ethernet
Ethernet	2 x RJ45
USB	1 x Type-C USB 3.0, 3 x USB 3.0, 2 x USB 2.0
Serial Port	4 x RS232, 2 x RS485
Audio	1 x MIC-IN, 1 x AUDIO-OUT
Mini-PCIe	1 x Full-size Mini-PCIe for mSATA 1 x Full-size Mini-PCIe for WiFi/BT/3G/4G
SIM	1 x SIM Slot
M.2	1 x M.2 (2242/2280) for SSD
Storage	1 x 2.5" SATA 1 x Full-size mSATA
JAHC	WatchDog Timer Auto Power On RTC Remote Control
Operation System	Windows 8.1/10 (64-bit)
Power Requirement	DC-IN/19V/3.42A
Dimensions (W x D x H)	260mm x 173.4mm x 38.5mm(10.24" x 6.83" x 1.52")
Fanless	Yes
Construction	Metal
Mounting	Desk/Wall Mounting, VESA Mounting Kit (JZ 300)
Color	Black
Operating Temperature	0°C ~ 40°C (32 °F ~ 104 °F) at 0.7m/s Air Flow
Relative Humidity	95% @ 40°C (non-condensing)
Certification	CE, FCC Class B, CCC

Order Information

DE67-N1-7100U3000G	CPU: Core i3-7100U GPU: Intel® HD Graphics 620
DE67-N1-7200U3000G	CPU: Core i5-7200U GPU: Intel® HD Graphics 620
Packing List	2 x WiFi Antenna, 1 x Drive Disk, 1 x User Manual, 1 x AC Power Cable, 1 x AC Power Adapter
Optional Item	VESA Mounting Kit (JZ 300)

Dimensions and Drawing

